

Famed Żywiec reserves the right to change the prices in any moment within the validity of the Price-list.

The below price list is confidential and cannot be disclosed to other parties. The prices given are net prices, without installation, commissioning, training. Maintenance costs EXW Żywiec, Poland (INCOTERMS 2020).



www.famed.com.pl



+48 33 866 63 75
















export@famed.com.pl



| | Product name | Type | Unit price (EUR) |
|---|--|----------|------------------|
|  | <p>NEXO hospital bed COMFORT version with PLASTIC head/foot boards Fully electric hospital bed with pantograph structure, with SoftDropPlus™ side rails (divided, full length, made of PLASTIC with inserts BLUE TRIANGLES, without controls) WIRE REMOTE CONTROLLER & CONTROL PANEL, CENTRAL BRAKE SYSTEM</p> | NEXO | 2 217 |
|  | <p>Brake alarm</p> | WL-99.68 | 460 |
|  | <p>Foot controller: rev-Trend, height adjustment, examination pos. (1pce)</p> | PL-63.67 | 150 |
|  | <p>USB port</p> | WL-99.75 | 105 |
|  | <p>Mattress in a waterproof, steam permable cover (Dahlia T70 white) thickness 12 cm</p> | MC-28.05 | 182 |
|  | <p>Mattress in a waterproof, steam permable cover (Dahlia T70 white) thickness 16 cm</p> | MC-28.5 | 231 |

| | | | |
|---|---|----------------|-----|
|  | Additional mattress in steam permeable cover (Dahlia T70 white) for bed pallet extension, for mattress with thickness 12cm | MC-47.1 | 72 |
|  | Additional mattress in steam permeable cover (Dahlia T70 white) for bed pallet extension, for mattress with thickness 16 cm thickness | MC-47.0 | 77 |
|  | Passive anti-decubitus mattress in a waterproof, steam, permeable cover (Dahlia T70), thickness 12cm | MP-01.11 | 358 |
|  | Passive anti-bedsore mattress Hyper Foam Plus Greenline up to stage III of pressure ulcers according to EPUAP, moderate risk (Norton, Braden, Waterlow Scale). Applicable for pain therapy. Mattress with dimensions of 850x2000 mm, height: 140 mm. For patients weighing between 20 and 140 kg. | HFPlus | 400 |
|  | Passive anti-bedsore mattress Hyper Foam Plus Clinic Greenline up to stage III of pressure ulcers according to EPUAP, moderate risk (Norton, Braden, Waterlow Scale). Applicable for pain therapy. Mattress with dimensions of 850x2000 mm, height: 140 mm. Clinic version: firm edges provide stability, ultrasonically welded seams. For patients weighing between 20 and 140 kg. | HFPlus Clinic | 430 |
|  | Passive anti-bedsore mattress Hyper Foam 2 Greenline up to stage IV of pressure ulcers according to EPUAP, very high risk (Norton, Braden, Waterlow Scale). Applicable for pain therapy. Mattress with dimensions of 850x2000 mm, height: 150 mm. For patients weighing between 20 and 150 kg. | HF2 GL | 500 |
|  | Passive anti-bedsore mattress Hyper Foam 2 Clinic Greenline up to stage IV of pressure ulcers according to EPUAP, very high risk (Norton, Braden, Waterlow Scale). Applicable for pain therapy. Mattress with dimensions of 850x2000 mm, height: 150 mm. Clinic version: firm edges provide stability, ultrasonically welded seams. For patients weighing between 20 and 150 kg. | HF2Clinic GL | 530 |
|  | Passive anti-bedsore mattress MAXX250 Greenline up to stage IV of pressure ulcers according to EPUAP, very high risk (Norton, Braden, Waterlow Scale). Applicable for pain therapy. Mattress with dimensions of 850x2000 mm, height: 180 mm. For patients weighing max. 250 kg. | MAXX250 | 540 |
|  | Passive anti-bedsore mattress MAXX250 Clinic Greenline up to stage IV of pressure ulcers according to EPUAP, very high risk (Norton, Braden, Waterlow Scale). Applicable for pain therapy. Mattress with dimensions of 850x2000 mm, height: 180 mm. Clinic version: firm edges provide stability, ultrasonically welded seams. For patients weighing max. 250 kg. | MAXX250 Clinic | 590 |

| | | | |
|---|--|----------------|-------|
|  | <p>Decubitus therapy mattress with evacuation function EvaQ PRO II Greenline - all-in-one solution. Passive anti-bedsore mattress up to stage IV of pressure ulcers according to EPUAP, very high risk (Norton, Braden, Waterlow Scale). Applicable for pain therapy. Equipped with an evacuation functions. Mattress with dimensions of 850x2000 mm, height: 150 mm. For patients weighing up to 150 kg.</p> | EvaQ PRO II GL | 560 |
|  | <p>EvaQ PRO XL Greenline Decubitus therapy mattress with evacuation function EvaQ PRO XL - all-in-one solution. Passive anti-bedsore bariatric mattress up to stage IV of pressure ulcers according to EPUAP, very high risk (Norton, Braden, Waterlow Scale). Applicable for pain therapy. Equipped with an evacuation functions. Mattress with dimensions of 850x2000 mm, height: 180 mm. For patients weighing up to 250 kg.</p> | EvaQ PRO XL | 630 |
|  | <p>Hyper AIR hybrid anti-bedsore mattress up to stage IV of pressure ulcers according to EPUAP, very high risk (Norton, Braden, Waterlow Scale). Applicable for pain therapy. Mattress with dimensions of 860x1960 mm, height: 160 mm. Bottom layer and firm edges to provide stability made of foam. Top plate made of hybrid foam. Core of mattress made of 8 foam-filled air cells for ideal comfort in the area most prone to pressure ulcer development - no risk of failure due to self-inflating foam-in-cell technology No electricity required. Maintenance-free. For patients weighing between up to 250 kg.</p> | HYPER AIR | 960 |
|  | <p>CARESAFE™ Active therapy, automatic air mattress with foam underlay and pump. Therapeutic mattress system with smart pressure redistribution with alternating and continuous low pressure therapy, according to individual needs and clinical indications. 17 individual air cells, separately replaceable. 2 main body zones and a head pillow function in the head zone. Unique air distribution system in the heel zone that deflates cells to zero pressure. Total hygienic safety and skin microclimate assistance - welded, two-way stretch, breathable cover, fully protected foam. Robust bottom ticking featuring securing straps and loops for power cable management. Pump: Air output: 8 liter / min. Pressure range: 20 mmHg - 55mmHg Mattress: Dimensions of the mattress: 85 cm (W) x 200 cm (L) x 20 cm (H) consists with: 12,5 cm of air-cells + 7,5 cm of foam underlay Safe working load: 250 kg</p> | CARESAFE | 1 500 |
|  | <p>Side rails height extender (4pcs)</p> | PL-60.0 | 292 |
|  | <p>Tunnel for X-ray cassette with tray, under the back rest segment (1 pce)</p> | PL-18.5 | 88 |
|  | <p>Double extension apparatus</p> | RW-09 | 1 144 |

| | | | |
|---|---|----------|-----|
|  | Fifth wheel (1 pce) | PK-01.3 | 242 |
|  | Indicator of bed pallet inclination (2 pcs) | PL-24.4 | 105 |
|  | Holder for oxygen bottle (1 pce) on head/foot board | PL-36.6 | 193 |
|  | Shelf for bed clothes and VEM panel (1pce) | PL-67.67 | 127 |
|  | Shelf for medical devices (350x 250 mm) | WL-63.03 | 138 |
|  | Lifting pole, varnished (1 pce) | UR-07.2 | 105 |
|  | Drip bottle holder made of stainless steel /2 hooks, 2 baskets/ (1 pce) | WK-12.0 | 138 |
|  | Drip bottle holder /4 hooks/ (1 pce) | WK-17.0 | 121 |
|  | Urinal holder (1 pce) | WL-19.7 | 39 |

| | | | |
|---|--|---------|-----|
|  | Holder for bedpen (1 pce) | WL-20.8 | 39 |
| | Holders for belts mounting (2 pieces of holders with connecting elements) (1 set) | UPWW12 | 22 |
| | Patient fastening belt WW-12 (1 set) concerns beds | WW-12.0 | 84 |
|  | Plastic hook for fluids (1 pce) | WL-18.1 | 22 |
| | Two additional wheels locking levers on the head side | PL-14.0 | 149 |
| | Set of decorative inserts (available colours: RAL 5012, RAL 5002, RAL 6019, RAL 1015) Possibility of personalize grafics to inserts for extra charged special request | PL-12.0 | 72 |
|  | Shelf foldable mounted on the footboard of the bed | WL-94.4 | 171 |
|  | Bedside locker SP-02.0 with additional table top | SP-02.0 | 642 |
|  | Bedside locker | SP-02.2 | 409 |

| | | | |
|---|--|----------------|------------|
|  | <p>Easy lift over bed table ERGO</p> <p>Steel construction powder coated Table top surface covered with plastic (ABS) Easy lift, full mechanical height adjustment Modern ABS plastic base cover Tilt section angles: 24, 31, 37, 42, 47 Safe working load: 25 kg evenly distributed Height adjustment: 753 to 1061 mm</p> | <p>ERGO</p> | <p>583</p> |
| | <p>Basket for two bottles 1,5l (concerns SP bedside lockers)</p> | <p>WT-06.0</p> | <p>72</p> |
|  | <p>Railing with hooks (concerns SP bedside lockers)</p> | <p>WT-07.0</p> | <p>22</p> |