

CARDIO M CARDIO M-PLUS

Compact multi-channel electrocardiograph



Affordable and Powerful 12ch Resting ECG

CARDIO M and CARDIO M PLUS of medical ECONET offer a wide range of innovative solutions for diagnostic ECG acquisition.

A standard 12-lead electrocardiogram, also known as an ECG, is one of the standard tests used to measure the electrical activity of the heart muscle. It's non-invasive, painless, and quick and it's considered one of the best ways to assess heart disease risk.

An ECG is typically used as a baseline test for new patients or for anyone showing symptoms of heart disease. While the average person doesn't need to undergo the procedure very often, those who smoke, have high cholesterol, or have a family history of heart disease should consult with their doctor to see how often they should get tested.

A normal ECG can be a great reassurance that your heart is functioning well and working harmoniously with your body to contribute to your good health.



Features of CARDIO M

- Exact measurement with interpretation
- Print out in A4 format
- Supports fax transmission of the recorded ECG (with optional modem)
- PC software for computer connection
- Rechargeable battery (optional)

Features of CARDIO M-PLUS

- Touch screen operation (Full alphanumeric keyboard support)
- 7" color TFT LCD screen (800X480) with 12CH preview
- Preview function before printing paper
- Long term ECG recording & automatic arrhythmia detection
- Special reports for detailed interpretation (Beat, Guide, Vector)
- Internal memory for 200 ECGs
- Various ECG formats:
 XML, PDF, MFER, DICOM, ECG
- Diagnosis form 1st postnatal day (pediatrics)
- Expression on A4 size paper
- USB Wifi converter (optional)
- Free software
- High capacity rechargeable Li-lon battery for min. 3 hours operation (optional)

CARDIO M CARDIO M-PLUS

Compact multi-channel electrocardiograph


The Main Function of CARDIO M and CARDIO M-PLUS

Having good cardiovascular health is an important factor of optimal wellness. Your heart works as a "pump" to keep your blood moving inside of you, to deliver nutrients and oxygen to all areas of your body while carrying away waste products and carbon dioxide. When your heart muscle contracts or "beats", it pushes blood through your heart and all over your body.

An ECG is a non-invasive test to measure the electrical activity of the heart beat and also provides information about heart muscle damage, types and kinds of arrhythmias (abnormal heart rhythms), and signs of a heart attack.







Standard 12-lead ECG


The overall magnitude of the heart's electrical potential is then measured from twelve different angles and is recorded over a period of time.

WIde paper printing

Convenient A4 size print-outs allow for easy chart filling. Grid function allows you to use low cost plain fax paper. User can easily read information at a glance.

Reports for more detailed Interpretation

Detailed measurement data for professional interpretation. User can select Text, Guide, or Vector version. (only for CARDIO M-PLUS)





Extended data management

Up to 200 ECGs can be stored in the internal storge and USB memory. User can export data in various standard file format (PDF, JPG, ECG wave & large touch screen keyboard. XML, MFER, DICOM) (only for CARDIO M-PLUS)

User-friendly design

CARDIO M-PLUS 7 inch wide & clear color TFT LCD display with 12 channel preview (only for CARDIO M-PLUS)

Specifications

CARDIO M

CARDIO M-PLUS

im		

Size: 296 (W) x 305.5 (D) x 97.5 (H) mm

Weight: Approx. 3.2 kg

2 lines text LCD screen Display: 7" color TFT wide display (800 x 480)

Display

2 lines text LCD screen Type: 7" color TFT wide display (800 x 480)

Sensitivity, speed, flter status, HR, printing form, Monitor display: HR, ID, date, AC or battery state, sensitivity, speed, number of saved data, printing form, rhythm lead

rhythm lead

ECG

Leads: Standard 12 leads

5, 10, 20, auto (I ~ aVF: 10, V1 ~ V6: 5) mm / mV Sensitivity:

Hear t rate, PR, QRS, QT / QTc, P - R - T axes Basic measurement:

Recording channel: 1, 3, 6 and 12 channel

12 channel simultaneous ECG and acquisition 2.5, 5, 10, 20, auto (I~aVF: 10, V1~V6: 5) mm/mV

Heart rate, PR, QRS, QT/QTc, P-R-T axis

300 (W) x 299 (D) x 123 (H) mm

Approx. 4 kg

3 channels + 1 rhythm, 3 channels + 3 rhythm,

6 channels + 1 rhythm, 12 channels, 1 channel long time

(1 min, 3 min, 5 min, 10 min) and special reports

(text, guide, vector)

Recorder

Resolution:

Type: Thermal print head Thermal print head, thermal roll paper Printing speed:

12.5, 25, 50 mm / s 5, 12.5, 25, 50, 100 mm/s

204 mm (width) 215 mm (width) x 297 mm (Length) (A4 size) Paper:

> Vertical: 8 dots/mm Vertical: 8 dot/mm Horizontal: 16 dots/mm Horizontal: 16 dot/mm

Set-up

AC: 50 / 60 Hz, 20 dB or better 50/60Hz, - 20dB or better 25Hz to 35 Hz, 3 dB or better 25Hz to 35Hz, -3dB or better Muscle: Base line drift: 0.1 Hz, 3 dB or better 0.05, 0.1, 0.2 Hz, -3dB or better

Low pass filter: off, 40 Hz, 100 Hz, 150 Hz off, 40Hz, 100Hz, 150 Hz ID, name, age, sex, hight, weight Patient data: ID, name, age, sex, height, weight, smoke, race

CMRR: ≥ ± 100 dB ≥ ±105dB

Class I, Typ BF Saftey: Class 1, Type CF, CE, FDA, KFDA, CFDA, NCC

Electrical Feature

Internal noise: 20uV(p-p) max 20uV(p-p) max

Floating input, isolated and defibrillation protected Input circuit:

Input impedance: $\geq 10 M\Omega$ > + 5 mVinput range: > + 300 mV DC offset voltage:

Disconnected lead detection Signal quality control:

Time constant: 3.2 sec. 0.05~150Hz Frequency response: <10 μΑ Patient isolation:

Patient leakage current: ECG data storage:

Frequency response 0.05~150Hz within -3 db

Pacemaker pulse detection lead fault detection,

Isolated, defibrillation and ESU protected

 \geq 50 M Ω

 $\geq \pm 5 \text{mV}$

> +400 mV

signal saturation detection.

Internal storage for 200 ECGs and external USB flash drive

Indicator

Communication: PC connection by LAN RS232, LAN, WiFi, USB flash drive, USB barcode scanner

External link: LAN LAN, 2 USB Port

File format: PDF, JPG, XML, MFER, DCM

Specifications

CARDIO M

CARDIO M-PLUS

Environment Speecification

Operating temperature:	10°C to 40° C	10°C to 40° C
Operating humidity:	30% to 85%	30% to 85%
Atmospheric pressure:	70KPa to 106 KPa	70KPa to 106 KPa

Power

Power supply:	AC or built-in battery (option)
Power requirement:	100 - 240 VAC, 50 / 60 Hz, 1.0 - 0.5 A
Battery type:	Replaceable and rechargeable Lithium Ion
Battery capacity:	6 hours of continuous operation without printing

or approx. 100 automatic ECG printouts

AC or built-in battery (option)

100 - 240 VAC, 50/60 Hz, 1.0 - 2.0 A,

Replaceable and rechargeable Lithium Ion
6 hours of continuous operation without printing


or Approx. 3 hours of 200 ECG printouts

Accessory


Standard:	10-lead ECG patient cable	1 ea 10-lead ECG patient cable		1 ea
	Limb electrodes (4pcs / pack)	1 ea	Limb electrodes (4pcs / pack)	1 ea
	Chest electrodes (6pcs / pack)	1 ea	Chest electrodes (6pcs / pack)	1 ea
	Paper	1 ea	Paper	1 ea
	Gel	1 ea	Gel	1 ea

296 mm 305.5 mm





Packaging



Approx. 6.2 kg

Packaging



Approx. 6.3 kg

Accessory Information



ECG Cable Banana Type
31.10-2036



ECG Cable Clamp Type

for disp. electrodes 31.10-2035



Chest Electrodes

for adult, 6pcs / pack 31.10-2055



Chest Electrodes

for pediatric, 6 pcs / pack 31.10-2056



Limb Electrodes

4 pcs / pack 31.10-2054



Adapter for Disposable Electrodes

10 pcs / pack 31.10-2039



Disposable Electrodes

30 pcs / pack 70.10-3700



Roll Paper

A4 size, Length: 23 m Width: 21,5 cm 70.10-2021



Mouthpieces

100 pcs / box 70.10-3030



Callibration Pump

JL

41.20-3112



Rechargeable Battery

for CARDIO M-PLUS 36.11-4101



WIFI USB-dongle

for CARDIO M-PLUS 36.11-4105



Mobile Cart

with basket 31.10-3018



ECG Cable Arm

cable hanger 31.10-2041



Copyright @ 2020 medical ECONET All rights reserved



