

MEASURING INSTRUMENT

Thermo-hygrometer -20/+60 °C

Portable, simultaneous temperature and humidity display



DESCRIPTION

Portable thermometer-hygrometer with simultaneous dual display of temperature and relative humidity. Designed for fast ambient readings in medical, laboratory, pharmacy and logistics environments, it combines immediate hand-held operation with a high sampling rate of 2.5 readings per second.

Supplied ready to use, battery included.

TECHNICAL SPECIFICATIONS

Specification	Value
Temperature range	-20 to +60 °C (-4 to +140 °F)
Relative humidity range	10 to 100 % RH
Display	Dual-line LCD — temperature and humidity shown together
Temperature unit	°C / °F, user selectable
Sampling rate	2.5 readings per second
Functions	Data hold, min / max memory
Power supply	Battery supplied — low-battery indicator
Power saving	Automatic shut-off
Format	Portable, compact hand-held design

KEY BENEFITS

- Dual display: one instrument instead of two, ready to use out of the box.
- High sampling rate for a stable, responsive reading.
- Data hold and min / max tracking, low-battery indicator and automatic shut-off.

APPLICATIONS

- Laboratory monitoring
- HVAC/R installation and testing
- Warehouses and cold transport
- Environmental studies
- Food and beverage distribution
- Greenhouses, saunas, museums

Manufacturing and distribution — IBSGROUPE Ltd, as a turnkey supplier, handles the distribution, logistics, commissioning and after-sales service of this product. Manufacturing is carried out by the partner manufacturer, whose part numbers and specifications are reproduced above. *Non-contractual document: specifications may be changed by the manufacturer without prior notice; where the text and the illustration differ, the text prevails.*