

VICTORY HO HI-LOW

Customized model



VICTORY HO, hospital electric bed designed and recommended for environments with medium or high bacteriological risk. Robust 60x30x1.5mm steel frame with epoxy paint. Victory frame with four sections, three articulated and one fixed, with polymer fibre slats, which allow for easy disinfection and reduce bacteriological risks. Independent electrical articulation of the backrest and legs, through 6000N low-voltage motors suitable for hospital environments. Bed elevation by electric double H elevator (photo) or scissor elevator, guarantees robustness and lateral stability. Simple and intuitive user control. Detachable headboards and footboards in HPL (phenolic

compact, grey), for easy access and disinfection. Includes 3 plastic blockers to avoid movement of mattress. With wall protectors on 4 corners. Structure prepared for the application of 2 poles (ex. IV pole and monkey pole). 125mm ABS wheels (with double H elevator) or 100mm steel wheels (scissor elevator), 2 with brakes. Prepared for application of steel universal folding side rails with epoxy paint. Maximum user weight: 195Kg. SWL: 230Kg. CE Certification. Manufactured in accordance with EU hospital beds standards.

Option: Victory HO manual, with 2 cranks for manual operation of head and legs sections.

Features



Independent articulation

Independent motors for backrest and legs articulation and hi-lo



Disinfection

Polymer slats, suitable for environments with high bacteriological risk



Electric joystick

Easy and intuitive to use



Headboards

In HPL with metallic arch




Double H Hi-lo

Lifting by "double H" articulated arms guarantees robustness and lateral stability. 125mm ABS wheels



Scissor Hi-lo

Lifting by "scissor structure" with 100mm steel wheels



Side rails

Optional

Technical data

VICTORY HO HI-LOW

Manufacturer: Orthos XXI

Frame width	90cm	Legs angle	0°-33°
Frame length	196cm	Wheels double H/scissor	125/100mm
Total width	100cm	Structure colour	Beige
Total length	205cm	Slats	Polymer
Minimum height double H/scissor	42/41cm	Maximum user weight	195Kg
Maximum height double H/scissor	76/75cm	SWL (safe work load)	230Kg
Backrest angle	0°-71°		

Tolerance: +/-1cm

NOTE: in case of divergence between text and image, prevails the information described in the text. For continuous improvement, Orthos XXI reserves the right to make changes to its products without prior notice. More information available in the product manual.

Update: 04/20

Siège: 27, Old Gloucester Street, LONDON, WC1N 3AX, (UK) - Tél. +44 20 3398 1339

Bureaux: 15 rue de la Garenne 27950 Saint-Marcel (France) Tél. +33 1 87 66 35 60

<https://ibsgroupe.com> – Email: dircom@ibsgroupe.com

Turnkey Supplier