



ECOtwin LED

Modernized user-friendly antepartum fetal monitor



medical **ECONET**
GERMANY

- 7 segment LED display
- Easy data transfer through USB stick
- High sensitive 9 elements 0.985 MHz transducer
- Waterproof probes
- Built-in battery and printer
- Networkable with PC (RS-232C or optional Bluetooth)
- Including probes, bag, event marker, belts, gel and paper

Specifications

Ultrasound
Multicrystal transducer
Pulsed doppler
Ultrasound frequency : 0.985 MHz
Intensity: <10mW / cm ²
FHR range: 30 ~ 240 bpm
FHR accuracy: ± 2% of range
Dual doppler
Waterproof (IPX 8)
UC (Uterine Contraction)
External type
Frequency response: DC ~ 0,5 MHz
Reference (Zero) Control
Measurement range: 0 ~ 99
Waterproof IPX8
FM (Fetal Movement)
Detection method: Ultrasound
Dual FM
AST (Acoustic Simulator: Optional)
Vibration function waking fetus
Display
7 segment LED display
Heart rhythm
Printing state
Record speed: 1, 2, 3 cm / min
Auto Print 10, 20, 30, 40, 50, 60 min
Alarm on / off state LED
Sound
Doppler sound with volume control
HR sound
Key sound
Printer paper out
Probe fault
Low battery
Alarm sound

Printer
Thermal array z-fold type (width: 150 mm)
Record speed: 1, 2, 3 cm / min
Record contrast: mode 1, 2, 3
Auto record period : Off, 10, 20, 30, 40, 50, 60 min
Set-up
Alarms upper / lower value
Time & date
Print contrast 1, 2, 3
Print speed & zoom
FHR volume level
Function
Mark function
UC reference
Zoom in particular response
Signal Interface
RS-232 C serial interface
Bluetooth Central Interface (optional)
Environmental Specifications
Temperature range
Operating: 10 to 40 °C
Storage: -20 to 60 °C
Relative humidity range
Operating: 30 ~ 85 %
Storage: 20 ~ 90 %
Power Specifications
Power requirements: 100 - 240VAC, 50/60 Hz, about 80VA
Output: DC +15V 2.5A
Battery: rechargeable
Optional Accessories
Mobile trolley and wall mount

medical **ECONET**
GERMANY

Welcome to healthcare

Im Erlengrund 20, 46149 Oberhausen - Germany

CE 0123



*All specifications are subject to change without notice.